

KRM CORPORATION

OSHAS 19001-2007 & BS EN ISO 9001 : 2008 CERTIFIED COMPANY
to meet OSHA'S Lockout Tagout Standard 29 CFR, 1910.147&1910.269

GSTIN No.: 06AAVPW8746Q1Z6,
PAN No.: AAVPW8746Q
TIN No.: 06821328889,
TAN no.: RTKKO3359G

M: 00 91 9810 291 381, 8800 544 881

Regd. Office: 1H/31-A, N.I.T, Faridabad-121001 (Haryana) Postal Office: 615, Sector-15-A, Faridabad-121007-Haryana-NCR-INDIA

www.krmcorporation.com



LOCKOUT/TAGOUT
KRM-LOTO
SAFETY PRODUCTS

to compliance
OSHA'S Lockout Tagout Standard
29 CFR, 1910.147&1910.269

Email: info@krmcorporation.com, krm@krmcorporation.com, wadhwrajinder@gmail.com



www.lootoappliances.com

**KRM Safetech Private Limited**

GSTIN No.: 06AAECK2831L1ZI
PAN No.: AAECK2831L
TIN No.: 06824000112
CIN No.: u31903HR2011PTC042508

Telefax: 00 91 129 4021 381, 413 1381 (D)

www.lockouttagouts.com

www.lockouttagouts.com

www.safetyloto.com

www.lockoutmaster.com

www.lootoappliances.com

KRM LOTO – PLUG VALVE LOCKOUT

- Plug Valve Lockout is the main lockout device used to effortlessly and successfully secure a physically activated attachment valve with a stem width between 23 mm – 35 mm.
- The base of the lockout device can be set up once connected, and by and large does not meddle with valve actuation by torque or removable handle.
- Material - Poly Propylene
- Can be used at temperature at 31°C - 93°C.
- Adequately reasonable for the valves which are hard to lockout.
- Available in different sizes

KRM-K-PVL-01 – Suitable for valves with a stem diameter for 22 mm

KRM-K-PVL-02 – Suitable for valves with a stem diameter for 23 mm – 34 mm

KRM-K-PVL-03 – Suitable for valves with a stem diameter for 44 mm – 53 mm

KRM-K-PVL-04 – Suitable for valves with a stem diameter for 55 mm – 63 mm

- Color - Red or any color make as per volume.

**KRM-K-PVL**