



OEM Manufacturer & Global Supplier of
 Lockout Tagout & Safety Products

to meet
 OSHA'S Lockout Tagout Standard
 29 CFR, 1910.147&1910.269



www.lotoappliances.com



Regd. Office:1H/31-A, N.I.T, Faridabad-121001 (Haryana) Postal Office:615, Sector-15-A, Faridabad-121007-Haryana-NCR-INDIA

www.krmcorporation.com | www.lockouttagouts.com | www.krmloto.com | www.locktagindia.com | www.lotoappliances.com

KRM LOTO – ROUND MULTIPURPOSE CABLE LOCKOUT (8+8 HOLES)

- Cable lockout devices are extremely flexible and economical and can be used for multipurpose lockout that is a CE Certified product and made to follow OSHA standard.
- **Material** – ABS or Polypropylene and metal part made of standard steel finish with external threading.
- Bolt molded in the base part of polypropylene device having holes and upper part of polypropylene having internal threading for the upper screw.
- KRM LOTO Round Multi Purpose Cable Lockout used to tie the installed device for safety purposes that is made with two parts, Upper and lower – both parts are having holes 8 holes
- **Cable length** - 1.5 meter, 2 meter, 3 meter, 5 meter, 10 meter, 20 meter. Standard cable thickness is 4 mm, 5 mm available on request at additional cost.
- Can be utilized to lock ball valve, gate valve and other electrical equipment that is used for Electrical or mechanical group isolation.
- **Weight** – 40 gm for the body of the body and 70 gm of the cable for 2 mtr cable
- **Color** – Red, Yellow, Green, Blue Or as per the required quantity.



KRM-K-RMCLT-8CLWT
 (WITH CABLE & LOCKING DEVICE)




KRM-K-RMCLT-8CL
 (2 MTR CABLE WITH LOOP)



KRM-K-RMCLT-8C
 (2 MTR CABLE WITHOUT LOOP)



KRM-K-LTD-R/G/Y/B



MODELS	A	B	C	NO OF HOLES	WEIGHT
KRM-K-RMCLT-8CLWT	40 mm	15 mm	7.5 mm	8	130 gm
KRM-K-RMCLT-8CL	40 mm	15 mm	7.5 mm	8	110 gm
KRM-K-RMCLT-8C	40 mm	15 mm	7.5 mm	8	100 gm
KRM-K-RMCLT-8/8H	40 mm	15 mm	7.5 mm	8	40 gm
KRM-K-LTD	150 mm	30 mm	15 mm	1	30 gm