

GSTIN No.: 06AAPW8746Q1Z6,  
PAN No.: AAVPW8746Q  
TIN No.: 06821328889,  
TAN no.: RTKKO3359G  
IEC: 0509006116

M: 00 91 9810 291 381, 8800 544 881

Regd. Office: 1H/31-A, N.I.T, Faridabad-121001 (Haryana) Postal Office: 615, Sector-15-A, Faridabad-121007-Haryana-NCR-INDIA

[www.krmcorporation.com](http://www.krmcorporation.com) | [www.lockouttagouts.com](http://www.lockouttagouts.com) | [www.krmloto.com](http://www.krmloto.com) | [www.locktagindia.com](http://www.locktagindia.com) | [www.lotoappliances.com](http://www.lotoappliances.com)



OEM Manufacturer & Global Supplier of  
Lockout Tagout & Safety Products

to meet  
OSHA'S Lockout Tagout Standard  
29 CFR, 1910.147&1910.269

Lock Tag!!



[www.lotoappliances.com](http://www.lotoappliances.com)

safe loto



**KRM Safetech Private Limited**  
QUALITY MANAGEMENT SYSTEM ISO 9001:2015

GSTIN No.: 06AAECK2831L1Z1  
PAN No.: AAECK2831L  
TIN No.: 06824000112  
CIN No.: U31903HR2011PTC042508  
IEC: AAECK2831L

Telefax: 00 91 129 4021 381, 413 1381 (D)

## KRM LOTO – ECONOMY DI ELECTRIC CABLE LOCKOUT HASP

- Material** – ABS with metallic insulated cable Economical cable lockout easy to carry as it is lighter in weight, it can resolve the purpose of multiple application like cable locking as well as group isolation like hasp and other safety devices.
- It can be useful for lockout the electrical as well as mechanical installed devices hence it is a versatile device in nature and then Tagout by an authorized person.
- Insulated steel cable and multipurpose lock body is metallic from inside that is coated with ABS material having totally six holes for group lockout. steel die cut is available to insert and hold the insulated cable
- Complete Outer Size of multipurpose lock- length 147 mm, width of upper part is 10 mm and lower wide part is 13 mm, internal Hole diameter – 8 mm
- Weight** – 150gm
- Color** – Standard color Red or can make any color as per the quantity required.



**KRM-K-EDCLH+2C**

MODELS	Length	Width	Hole Dia	Lower Part Width	No of Holes	Weight
KRM-K-EDCLH+2C	147 mm	10 mm	8 mm	13 mm	6	150 gm