

KRM CORPORATION

IEC: 0509006116

GSTIN No.: 06AAVPW8746Q1Z6 PAN No.: AAVPW8746Q TIN No.: 06821328889, TAN no.: RTKKO3359G

KRM

OEM Manufacturer & Global Supplier of Lockout Tapout & Safety Products

XM DO

OSHA'S Lockout Tagout Standard 29 CFR, 1910.147&1910.269



Lock Tag!!



K&1 Safetech Private Limited

GSTIN No.: 06AAECK2831L1ZI

PAN No.: AAECK2831L TIN No.: 06824000112

CIN No.: U31903HR2011PTC042508

IEC: AAECK2831L

Telefax: 00 91 129 4021 381, 413 1381 (D)

M: 00 91 9810 291 381, 8800 544 881 Email: info@krmloto.com, info@krmcorporation.com, krmloto@gmail.com Regd. Office:1H/31-A, N.I.T, Faridabad-121001 (Haryana) Postal Office:615, Sector-15-A, Faridabad-121007-Haryana-NCR-INDIA

www.krmcorporation.com www.lockouttagouts.com

www.krmloto.com

www.locktagindia.com

www.lotoappliances.com

KRM LOTO-ROUND SHAPE METAL LOCKOUT

- Material Body made of metallic, attached with rivet.
- Round Shape metal lockout device is used to lock the racking inout point of air circuit breaker and Vacuum circuit breaker so that no one can operate the particular device, also can lock some sort of switches that are inserted inside a plain surface
- Made by riveting two pieces which can be easily rotated in any direction having three holes at bottom part to fix with the screw and also can be stuck with the strong double sided pre adhesive on requirement for locking purpose.
- Dimension Outer diameter is 65 mm, Inner diameter is 51 mm,
 - lower cover circle side width is 7 mm, overall thickness is 5 mm
- locking hole diameter is 8mm.
- Weight 70 gms
- Color Standard Color Grey.









KRM-K-RSML

MODELS	OUTER DIAMETER(A)	INNER DIAMTER(B)	WIDTH(C)	OVERALL THICKNESS(D)	LOWER THICKNESS	WEIGHT
KRM-K-RSML	65mm	51mm	07mm	5mm	03m	70gms