



OEM Manufacturer & Global Supplier of
Lockout Tagout & Safety Products

to meet
OSHA'S Lockout Tagout Standard
29 CFR, 1910.147&1910.269



www.lockoutappliances.com



KRM LOTO - GATE VALVE LOCKOUT DEVICE

- KRM-K-GVL-02 KRM LOTO Gate Valve Lockout is made by two parts these rotational valve covers can withstand in extreme weather conditions, resistant to cracking and abrasion that is valid for temperature range up to – 46°C to 177°C.
- It Surrounds the valve hand-wheel to prevent from being turned and protect against accidental operations.
- **Material** – Poly Propylene.
- **Model** – 2/3 holes locking option is KRM standard product
- **Size Applicable** – Suitable for:
 - KRM-K-GVL-02 for 25 mm to 63.5 mm (1" – 2.5") wheel diameter
 - KRM-K-2-GVL-02 for 25 mm to 63.5 mm (1" – 2.5") wheel diameter
 - KRM-K-3-GVL-02 for 25 mm to 63.5 mm (1" – 2.5") wheel diameter
 - **KRM-K-3GVL-02-MT for 25 mm to 63.5 mm (1" – 2.5") wheel diameter**
- **Color** – Standard color Red Or any color make as per volume
- **Weight** – 60gm

NOTE APPLICABLE FOR VALVE HANDLE - OUTER WHEEL DIAMETER NOT VALVE SIZE



KRM-K-GVL-02



KRM-K-2-GVL-02



KRM-K-3GVL-02-MT



KRM-K-3-GVL-02

MODELS	INSIDE DIAMETER	INSIDE HEIGHT	OUTSIDE DIAMETER	OUTSIDE HEIGHT	LOCK HOLE	WHEEL DIAMETER	NUMBER OF HOLES
KRM-K-GVL-02	66mm	36mm	80mm	42mm	9mm	25-63.5mm	1
KRM-K-2-GVL-02	66mm	36mm	80mm	42mm	9mm	25-63.5mm	2
KRM-K-3-GVL-02	66mm	36mm	80mm	42mm	9mm	25-63.5mm	3
KRM-K-3GVL-02-MT	66mm	36mm	80mm	42mm	9mm	25-63mm	3

