KRM CORPORATION SIO CARS - SHOP 2876, ISO EMS 1-860-12915, ISO CHISSING 45001-23116 ISO CARS - SHOP 2876, ISO EMS 1-860-12915, ISO CHISSING 45001-23116 ISO CARS - SHOP 2876, ISO CARS - ISO CHISSING 45001-2316 GSTIN No.: 06AAVPW8746Q1Z6

GSTIN No.: 06AAVPW8746Q1Z6, PAN No.: AAVPW8746Q TIN No.: 06821328889, TAN no.: RTKKO3359G

M: 00 91 9810 291 381, 8800 544 881

IEC: 0509006116



OEM Manufacturer & Global Supplier of Lockout Tagout & Safety Products

to meet OSHA'S Lockout Tagout Standard 29 CFR, 1910.147&1910.269





safe lêto

KM Safetech Private Limited

GSTIN No.: 06AAECK2831L1ZI PAN No.: AAECK2831L

TIN No.: 06824000112 CIN No.: U31903HR2011PTC042508

IEC: AAECK2831L

Telefax: 00 91 129 4021 381, 413 1381 (D)

Email: info@krmloto.com, info@krmcorporation.com, krmloto@gmail.com

Regd. Office:1H/31-A, N.I.T, Faridabad-121001 (Haryana) Postal Office:615, Sector-15-A, Faridabad-121007-Haryana-NCR-INDIA

₩ Regd. Of www.krmcorporation.com

| www.lockouttagouts.com

www.krmloto.com

Lock Tag!!

www.locktagindia.com

www.lotoappliances.com

KRM LOTO - LOCK TAG PADLOCK NYLON SHACKLE - ECONOMY RANGE-5 LEVEL

- A Padlock is a detachable lock passed by an opening with U Shaped shackle used to protect against unauthorized or unwanted stealing.
 Provided with LOCKING MECHANISM used to lock the different devices.
- PADLOCK----Molded lock structure durability key system: DIFFER KEY, ALIKE KEY OPTION
- key System 5 level management. Max Combination differ key -400 nos. and repeat after that.
- Key retaining feature in unlocked. Position.
- Configuration key card label as well as lock label, easy to know personal ID indicating the corresponding padlock for easy management.
- Body Material Engineering material ABS
- Shackle Material Nylon black material shackle 6mm thick
 - **Key**: Brass with SS finish –one lock one key
- Cylinder Pin: normal internal Pin
- Color Red, Blue, Green, Yellow, Black.
- Weight 75gm (-+10%)
- STANDARD ENGRAVED ALPHABETS WITH NUMRICAL NUMBER ON LOCK BODY & KEY HEAD.

BODY	BODY	BODY	SHACKLE	SHACKLE	SHACKLE
HEIGHT(A)	WIDTH (B)	DEPTH (C)	HEIGHT (D)	WIDTH (E)	THICKNESS (F)
45 mm	42 mm	20 mm	40 mm	20 mm	6 mm



