



OEM Manufacturer & Global Supplier of
 Lockout Tagout & Safety Products

to meet
 OSHA'S Lockout Tagout Standard
 29 CFR, 1910.147&1910.269



www.lotoappliances.com

Email: info@krmloto.com, info@krmcorporation.com, krmloto@gmail.com

Regd. Office: 1H/31-A, N.I.T, Faridabad-121001 (Haryana) | Postal Office: 615, Sector-15-A, Faridabad-121007-Haryana-NCR-INDIA



LARGE PNEUMATIC LOCKOUT

- KRM Large Pneumatic Lockout isolates potentially hazardous energy without costly tool modifications or inconvenient in-line valves.
- **Material** – Poly Propylene.
- **Holes for Chord** – One hole of 25 mm diameter on both sides.
- **Locking Slots** – 4 holes to latch with lock for group isolation
- **Complete Outer Size** – Length - 194 mm and width 64 mm.
- **Inner Size** – Length 184 mm and width - 60 mm.
- **Weight** – 290 gm
- **Color** – Red or can make any color as per volume required



KRM-K-PLC-PN-2

MODEL	COMPLETE OUTER LENGTH/HEIGHT	COMPLETE OUTER WIDTH	INNER LENGTH	INNER WIDTH	NUMBER OF HOLE	HOLE DIA	WEIGHT
KRM-K-PLC-PN-2	LENTGH-194 HEIGHT-96mm	Center 94mm Bottom 64mm	LENTGH-186mm HEIGHT-88mm	Center-86mm Bottom 52mm	04hole	8.5mm	290gm